

# **3TAG PVC CARDS**

# For small items or specific features



Evolis 3TAG blank PVC cards are the ideal solution for hospitality and retail businesses when you need to highlight specific features (promotion, organic food, label, handmade, etc.) or to label small items (such as chocolates). Composed of 3 divisible parts, you can print different mini tags at the same time.

#### **ADVANTAGES**

The 3TAG cards are an easy, affordable and modular way to manage your communication. They can be used by themselves or in association with a standard tag. Additionally, as the cards are in PVC, they are flexible but very resistant and solid.

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

# **GENERAL SPECIFICATIONS**

- · Cards in PVC
- · 2 colors:

C4521: Blank White - Mirror finish


C8521: Blank Black - Matte finish

- · Compliant with ISO CR-80 (ISO 7810) standards
- · Dimension:

85.85 mm x 54 mm (3 3/8" x 2 1/8")

3 tags: 28.5 mm x 54mm (1 1/8" x 2 1/8")

· Thickness: 0.76 mm / 30 mil





# PRODUCT INFORMATION:

- PVC Cards
- · Blank WHITE or blank BLACK
- · 3 Tags
- 30 mil



#### COMPATIBILITY AND PACKAGING

PART#	COLOR	PACKAGE	ZENIUS / PRIMACY	PRIMACY2	EDIKIO ACCESS	EDIKIO FLEX	EDIKIO DUPLEX
C4521	WHITE	1 box of 100 cards	•	•	From S/N: 10000624280	•	•
C8521	BLACK	1 box of 100 cards	•	•	From S/N: 10000624280	•	•

# COMPATIBLE WITH EDIKIO ACCESSORIES

In particular with our H-Gripper Part# AC000009 in order to maintain one minitag with your standard CR80 tag card:





# STORAGE INFORMATION

The cards shall be capable of functioning for up to 2/3 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging. Temperature of storage must be between 15-30°C (59-86°F) and at RH between 10-60%. Once opened, avoid dust, direct sunlight, high humidity and high temperatures. Do not place near solvent or other chemicals.

### INSTRUCTIONS FOR USE

In order to optimize the printing quality and card durability:

- Do not print cards that are damaged, folded, dirty or deformed.
- $\boldsymbol{\cdot}$  Avoid touching the printable surface of the cards to preserve print quality.
- $\cdot$  Do not expose tags to strong sources of heat (deterioration possible from 60 °C / 140 °F). Avoid thermal shocks.
- · Avoid putting the printed labels in contact with fatty substances.
- $\cdot$  Do not clean the tags in a machine, with boiling water or abrasive detergent products. Preference should be given to cleaning with warm water (<60°C / 140°F) or with a neutral detergent diluted with water, and a microfibre cloth. Dry the tags thoroughly before using them.



