




For easy identification



Evolis pre-punched blank cards are the ideal support for outstanding printouts. Their flat surface ensures flawless moves under the print head (minimizing the risk of damage) and printouts with vivid colours and well-defined barcodes.


ADVANTAGES

These cards can be used in several cases to identify your visitors or your business partners by a simple and cost-effective way. For instance, in a punctual event, your visitors can wear their badges with a clip or a lanyard, and then be identified without a badge holder.

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

GENERAL SPECIFICATIONS

- · Cards in PVC, Blank White
- · Compliant with ISO CR-80 (ISO 7810) standards
- \cdot Dimension: 85.6 mm Length x 54 mm Width (3 3/8" x 2 1/8")
- · Thickness: 0.50 mm / 20 mil
- · Round hole: 5mm diameter





PRODUCT INFORMATION:

- PVC Cards
- · Blank White
- Round Hole
- 20 mil



COMPATIBILITY AND PACKAGING

PART#	PACKAGE	ZENIUS / PRIMACY	PRIMACY2
C4512	1 box of 100 cards	•	•*

^{*} Standard 100 cards hopper only

ID ACCESSORIES COMPATIBLE WITH PRE-PUNCHED CARDS

· Plastic Croco Clips Part# 1413000



· Lanyards with metal hook (dog or swivel)



STORAGE INFORMATION

The cards shall be capable of functioning for up to 2/3 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging.

Temperature of storage must be between 15-30°C and at RH between 10-60%.

Once opened, avoid dust, direct sunlight, high humidity and high temperatures.

Do not place near solvent or other chemicals.

INSTRUCTIONS FOR USE

In order to optimize the printing quality and card durability:

- \cdot Do not use cards that have been damaged, folded or dropped on the floor.
- \cdot Do not touch the printable surface of the cards in order to preserve print quality.
- · Do not use in high temperature conditions. Do not place near heat sources. Avoid thermal shock.



